RUSTIC



Rustic Screen offers the perfect blend of natural texture and light control, made with 16% linen and a 5% openness factor. This flame-retardant fabric is available in versatile colors with a timeless aesthetic.

Physical properties

Composition	66% PVC - 18% PES - 16% LI
Type of finish/coating	No finish / coating
Thickness	0.52 mm
Weight	358 g/m2
Openess factor	5 %
Coloring	Yarn coated
Weave type	Basket 2x2
Threads warp solid	19 p/cm
Threads weft solid	18 p/cm
Yarn composition warp solid	Filament
Yarn composition weft solid	Filament
Available roll widths (cm)	300


Handling


Applicability	Roller, Panel
Processing	Cold cut, Ultrasonic cut
Processing direction	Drop for drop, Width for drop
Cleaning	Damp cloth, Dry cloth
Printable	No
Welding	Possible without tape/with welding tape V22-10(-A)


Certification data


Color fastness standard	ISO 105-B02
Color fastness value	7-8
Flame retardant	Yes
Flame retardant standard	AS 1530.2-1993, AS 1530.3 -1999, DIN 4102, EN 13773, NFPA 701
Oeko-Tex standard	Yes, 2208194
Greenguard certification	No
Greenguard gold certification	No
Trevira CS	No
Anti microbial	No
Moisture proof	Yes
Recyclable	No


Collections



01


02


03


04


05


06

RTA Specifications

		Thermal comfort										Visual comfort						
Article color code	Color	Rs	Ts	As	T-UV	Gtot int glazing C Value	Gtot int glazing C Class	FC glazing C Value	Gtot int glazing D Value	Gtot int glazing D Class	FC glazing D Value	Rv	Tv	Av	Glare control Class	Privacy night Class	Visual contact Class	Daylight utilisation Class
01	Linen	0,5828	0,2585	0,1587	0,0911	0,38	1	0,65	0,26	2	0,81	0,6552	0,222	0,1228	0	1	1	2
02	Sand	0,4842	0,2379	0,278	0,094	0,42	1	0,70	0,27	2	0,84	0,5237	0,1926	0,2836	0	1	2	2
03	Beige	0,3945	0,1821	0,4234	0,0858	0,44	1	0,75	0,27	2	0,86	0,4138	0,1428	0,4434	0	1	2	2
04	Limestone	0,3397	0,1697	0,4906	0,0975	0,46	1	0,78	0,28	2	0,87	0,3508	0,1361	0,5131	0	1	2	2
05	Clay	0,2383	0,1012	0,6605	0,0715	0,49	1	0,83	0,29	2	0,9	0,2488	0,0901	0,661	0	1	3	1
06	Anthracite	0,1263	0,0926	0,7811	0,0807	0,53	0	0,9	0,3	2	0,93	0,1304	0,0908	0,7788	0	1	3	1

Article color codes are subjected to availability of their respective product types. Please consult the webshop on My Coulisse for current supply.
The following regulations apply to the values listed in the table:

- Reflection, Transmission and Absorbtion EN 410:2011
- Gtot int glazing EN 52022-1
- Visual comfort classifications EN 14501:2021
- FC value EN 13363-1

The information in this productsheet is for guidance only and is based on information available at the time of publication. We want to emphasize that it is important to always consult the most recent product specifications for specific and detailed information about our range. Although this collection book has been compiled with the utmost care, we cannot guarantee the completeness, accuracy or timeliness of the information. Use of this information is entirely at the user's own risk. We accept no liability for any direct or indirect damages resulting from the use of this information.

If you have any questions about our products, please do not hesitate to contact us. Our team of experts is ready to help and inform you about our products and their specifications.

About Coulisse

We are a down-to-earth family run business founded in the Netherlands, built on strong partnerships. Working with and for passionate people to create the most forward-thinking window covering solutions for the industry worldwide. With our in-house engineers, quality department, R&D, creative marketing and e-business teams, we go above and beyond for our clients.

Contact us

EMEA
Vonderweg 48
7468 DC Enter
The Netherlands

Americas
2400 NW 116th St Suite 600
Miami FL 33167
United States

APAC
Unit 17/69 O'Riordan Street
Alexandria NSW 2015 Sydney
Australia

COULISSE
since 1992